

BEST AVAILABLE COPY

THOMSON
DELPHION

RESEARCH

PRODUCTS

INSIDE DELPHI

[Log On](#) | [Product](#) | [About Delphion](#)[My Account](#) | [Products](#)Search: [Quick/Number](#) [Boolean](#) [Advanced](#)

The Delphion Integrated View

Get Now: PDF | [More choices...](#)Tools: Add to Work File: Create new WorView: INPADOC | Jump to: [Top](#) Go to: [Derwent...](#)[Email](#)**>Title:** **JP9330707A2: ROLLER FOR CLOSELY CONTACTING LITHIUM FOIL MANUFACTURE****Country:** JP Japan**Kind:** A**Inventor:** TONOHARA KOUJI;**Assignee:** FUJI PHOTO FILM CO LTD[News](#), [Profiles](#), [Stocks](#) and More about this company**Published / Filed:** 1997-12-22 / 1996-06-10**Application Number:** JP1996000147330**IPC Code:** H01M 4/08; H01M 4/04;**Priority Number:** 1996-06-10 JP1996000147330**Abstract:**

PROBLEM TO BE SOLVED: To impart a sufficient close contact strength to a lithium foil with a small pressure contacting force by knurling the outer circumferential surface of a resin-made roller for closely adhering the lithium foil to an electrode plate.

SOLUTION: This roller 10 has a metallic shaft core 14 having a knurling 12 on the outer circumferential surface and a cylindrical body 16 made of a resin such as super-high density polyethylene or polypropylene to which the shaft core 14 is press fitted. The outer circumferential surface of the cylindrical body 16 has a knurling 18, and a plurality of hole part 19 are also formed thereon according to requirement. The roller 10 is arranged on one surface 26a side of a lengthy electrode plate 26 continuously carried in an arrowed direction A in order to intermittently apply an active material to a hoop-like copper foil support body at fixed intervals and stick a lithium foil 28 which is a thin metal foil adhesive to metal to the surface of 26a at a prescribed pitch. A nip roller 40 is arranged on the other surface 26b of the electrode plate 26 in such a manner as to approach to and retreat from the surface 26b.

COPYRIGHT: (C)1997,JPO**Family:** None**Other Abstract Info:** CHEMABS 128(07)077594R CAN128(07)077594R DERABS C98-107103 DERC98-107103Inquire
Regarding
Licensing



[this for the Gallery...](#)

© 1997-2003 Thomson Delphion [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)



(19)

(11) Publication number:

09

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 08147330

(51) Int'l. Cl.: H01M 4/08 H01M 4/04

(22) Application date: 10.06.96

(30) Priority:

(43) Date of application
publication: 22.12.97(84) Designated contracting
states:

(71) Applicant: FUJI PHOTO FILM CO

(72) Inventor: TONOHARA KOUJI

(74) Representative:

**(54) ROLLER FOR
CLOSELY CONTACTING
LITHIUM FOIL AND ITS
MANUFACTURE**

(57) Abstract:

PROBLEM TO BE SOLVED: To impart a sufficient close contact strength to a lithium foil with a small pressure contacting force by knurling the outer circumferential surface of a resin-made roller for closely adhering the lithium foil to an electrode plate..

SOLUTION: This roller 10 has a metallic shaft core 14 having a knurling 12 on the outer circumferential surface and a cylindrical body 16 made of a resin such as super-high density polyethylene or polypropylene to which the shaft core 14 is press fitted. The outer circumferential surface of the cylindrical body 16 has a knurling 18, and a plurality of hole part 19 are also formed thereon according to requirement. The roller 10 is arranged on one surface 26a side of a lengthy

electrode plate 26 continuously carried in an arrowed direction A in order to intermittently apply an active material to a hoop-like copper foil support body at fixed intervals and stick a lithium foil 28 which is a thin metal foil adhesive to metal to the surface of 26a at a prescribed pitch. A nip roller 40 is arranged on the other surface 26b of the electrode plate 26 in such a manner as to approach to and retreat from the surface 26b.

COPYRIGHT: (C)1997,JPO

